T36

Compact, Series 2 34.2 ps





Packed with features to help accomplish your goals

Take on harder tasks in smaller spaces with the T36, designed to be compact, proven to be durable and engineered to be efficient. This tractor is a workhorse in greenhouses, orchards and more.



1. DPF regeneration button



4. Digital Instrument Panel



2. Shuttle lever



5. PTO on/off switch



3. ROPS





6. Main shift lever



High torque, water-cooled Yanmar diesel engine

The Japanese made Yanmar engine offers more torque with less revs compared to competitors in its class. Since it is water cooled, the engine warms up faster and stabilized temperature more effectively while the tractor is running. The engine is also Tier 4 certified, including for noise emission standards.



Easy to open hood for convenient maintenance

The tractor hood can be opened in one motion, providing easy access to the engine and other systems for daily checks, routine service and maintenance. The side panel can also be removed easily without the need for specialized tools.



Dual filter air cleaner for engine longevity

The tractor comes with an additional filter to protect the engine of the tractor from harmful particles, drastically extending the engine life.



Cast iron components for sturdier connections

To perform durably with heavier loads, the rear of the rear of this tractor features sturdy cast-iron components to connect implements. The material enhances efficiency of the hydraulics and helps increase component lifecycles.



3-point hitch with powerful lift capacity

The 3-point linkage on the rear has an impressive lift capacity that reaches the end ball joints. The rear PTO control can be used to adjust rpm based on the task, increasing it for more intensive applications like slashing and digging.



High capacity fuel tank to support time intensive work

The high capacity fuel tank allows drivers to take on jobs for longer periods without stopping for fuel. This is in addition to the engine, which promotes fuel-efficient operation and increases the time before a refuel.

Technical specifications

ENGINE	
Engine manufacturer	Yanmar 3TNV88C (KKTF)
Туре	Natural Aspiration
Gross engine power	34.2 ps
PTO power	26.4 ps 19.7 kW
Rated engine speed	2800 rpm
No. of cylinders	3
Displacement	100.2 cu. in. 1642 cc
Air cleaner	Dual Dry
Alternator	12V, 70A
Fuel system	DI
POWERTRAIN	
Transmission type	Mechanical
No. of speeds	F12 x R12
Max. traveling speed	15.41 mph 24.8 km/h
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry Disc
CAPACITIES	
Fuel tank	8.71 gal 33 L
Coolant	7.4 qt 7.0 L
Crankcase	6.0 qt 5.7 L
Transmission/Hydraulics system	8.5 gal 32 L
Front axle	8.7 qt 8.2 L

РТО	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540/750/1000
HYDRAULIC SYSTEM	
Pump type	Dual Gear Pump
Implement flow	6.1 gpm 23.09 lpm
Steering flow	4.4 gpm 16.65 lpm
Total flow	10.5 gpm 39.7 lpm
Category, 3-point hitch	Cat1
Hitch lift capacity	2638.93 lb 1197 kg
Hitch lift capacity at 24 inches behind link ends	1558 lb 706 kg
Lift control type	Position
No. of standard remote valves	4 port
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	118.5 in. 3010 mm
Overall width	55.51 in. 1410 mm
Wheelbase	64.56 in. 1640 mm
Min. ground clearance	14.17 in. 360 mm
Min. turn radius with brakes	94.4 in. 2400 mm
Min. turn radius without brakes	116 in. 2950 mm
Height to top of ROPS	101.96 in. 2590 mm
Track width	F: 1137 mm / R: 1040 mm
Weight with ROPS	58.07 lb 1475 kg
STANDARD TIRES	
Agricultural - Front	8.0 - 16
Agricultural - Rear	12.4 - 24



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world